Serial No.: 10/500,404 Art Unit: 2617

AMENDMENTS TO THE CLAIMS:

This listing of the claims will replace all prior versions, and listings, of the claims in this application:

Listing of Claims:

1. (CURRENTLY AMENDED) A method comprising node:

specifying nodes present within a communication zone of a mobile node which moves among the specified nodes;

counting the number of <u>nodes present within each overlapping region</u> overlaps between a communication zone of <u>the mobile node</u> one of the specified nodes and communication zones of <u>each of the other</u> specified nodes for each specified node; and

selecting, as a candidate node for <u>next</u> communication with the mobile node next, the specified node in <u>the communication zone of</u> which the largest number <u>of nodes have</u> has been counted, wherein the mobile node performs said specifying, said counting, and said selecting, the specified nodes dispersedly arranged.

2. (CURRENTLY AMENDED) A method comprising:

specifying <u>neighbor nodes</u> a neighbor node present within a communication zone of a mobile node;

specifying neighbor nodes for each specified neighbor node of the mobile node that are present within a communication zone for a corresponding one of the specified neighbor nodes of the mobile node;

counting the number of specified neighbor nodes that are within the communization of the corresponding one of the specified neighbor nodes of the mobile node;

specifying a neighbor node present within a communication zone of the neighbor node; counting the a number of the specifications for each neighbor node; and

selecting, as a candidate node for <u>next</u> communication with the mobile node, <u>the specified</u> neighbor node of the mobile node having the largest number of specified neighbor nodes that are <u>within its communication zone</u> the neighbor node in which the number of the specifications in a predetermined order is large, wherein the mobile node moves among the neighbor nodes, the neighbor nodes being dispersedly arranged, wherein the mobile node performs said specifying the neighbor node with the communication zone of the mobile node, said specifying the neighbor node with the communication zone of the neighbor node, said solecting.

Serial No.: 10/500,404 Art Unit: 2617

3. (CURRENTLY AMENDED) The method according to claim 1, wherein the selection is not

performed if the specified node in the communication zone of which the largest number of nodes

have has been counted is the same as a node with which the mobile node is currently in

communication.

4. (CURRENTLY AMENDED) The method according to claim 3, wherein when there are a

plurality of specified nodes in the communication zone of which the largest number has been

counted, an arbitrary one node is selected.

5. (PREVIOUSLY PRESENTED) The method according to claim 1, wherein the mobile node

performs said specifying, said counting, and said selecting at predetermined periods.

6. (CURRENTLY AMENDED) The method according to claim 2, wherein the mobile node

performs said specifying the neighbor nodes present within node with the communication zone of

the mobile node, said specifying the neighbor <u>nodes present within the communication zones of</u>

the neighbor nodes node with the communication zone of the neighbor node, said counting, and

said selecting at predetermined periods.

7. (PREVIOUSLY PRESENTED) The method according to claim 5, wherein the predetermined

period is changed in accordance with a movement speed of the mobile node.

8. (PREVIOUSLY PRESENTED) The method according to claim 5, wherein the predetermined

period is changed in accordance with an arrangement density of the specified nodes.

9. (PREVIOUSLY PRESENTED) The method according to claim 1, wherein the specified nodes

are mobile nodes.

10. (PREVIOUSLY PRESENTED) The method according to claim 2, wherein the specified

nodes are mobile nodes.

11. (CURRENTLY AMENDED) The method according to claim 1, wherein the method selects a

<u>node</u> note without using a received signal strength indicator (RSSI).

3

Serial No.: 10/500,404

Art Unit:

2617

12. (CURRENTLY AMENDED) The method according to claim 2, wherein the method selects a

node note without using a received signal strength indicator (RSSI).

13. (PREVIOUSLY PRESENTED) The method according to claim 1, wherein the specified

nodes are uniformly dispersedly arranged.

14. (PREVIOUSLY PRESENTED) The method according to claim 2, wherein the specified

nodes are uniformly dispersedly arranged.

15. (CURRENTLY AMENDED) An apparatus comprising:

a wireless transmitter; and

a processor operable to specify nodes present within a communication zone of a mobile

node which moves among a plurality of nodes dispersedly arranged the specified nodes; count the

number of nodes present within each overlapping region a number of overlaps between a

communication zone of one of the mobile node of one of the specified nodes and communication

zones of other each of the specified nodes for each specified node; and select, as a candidate node

for <u>next</u> communication with the mobile node next, the specified node in the communication

zone of which the largest number of nodes have has been counted, wherein the mobile node

performs said specifying, said counting, and said-selecting, the specified nodes dispersedly

arranged.

16. (CURRENTLY AMENDED) The apparatus of claim 15, wherein the apparatus is the mobile

node which moves among a plurality of the specified nodes.

17. (CURRENTLY AMENDED) The apparatus of claim 16, wherein the method processor is

operable to select the candidate node for communication without using a received signal strength

indicator (RSSI).

18. (PREVIOUSLY PRESENTED) The apparatus of claim 17, wherein the specified nodes are

4

Serial No.: 10/500,404 Art Unit: 2617

mobile nodes.